


... designed primarily for wideband, large-signal output and driver amplifier stages in the 2 to 30 MHz frequency range.

- Designed for Class A, AB or C Power Amplifiers
- Specified 50 Volt, 28 MHz Characteristics:
 - Output Power — 150 Watts PEP
 - Power Gain — 15 dB Min, Class AB
- 100% Tested for Load Mismatch at all Phase Angles with $\infty:1$ VSWR
- Gold Metallization for Improved Reliability
- Diffused Ballast Resistors

2-30 MHz
150 WATTS PEP
50 VOLTS
SSB POWER
TRANSISTOR
NPN SILICON



MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CEO}	55	Vdc
Collector-Base Voltage	V_{CBO}	110	Vdc
Emitter-Base Voltage	V_{EBO}	4	Vdc
Collector Current — Continuous	I_C	15	Adc
Total Device Dissipation ($\theta_C = 25^\circ\text{C}$ Derate above 25°C)	P_D	300 2	Watts $W/^\circ\text{C}$
Operating Junction Temperature	T_J	200	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 65 to + 150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	0.5	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage ($I_C = 50 \text{ mA}, I_B = 0$)	$V_{(BR)CEO}$	55	—	—	Vdc
Collector-Base Breakdown Voltage ($I_C = 100 \text{ mA}, I_E = 0$)	$V_{(BR)CBO}$	110	—	—	Vdc
Emitter-Base Breakdown Voltage ($I_E = 5 \text{ mA}, I_C = 0$)	$V_{(BR)EBO}$	4	—	—	Vdc

ON CHARACTERISTICS

DC Current Gain ($I_C = 1 \text{ A}, V_{CE} = 5 \text{ V}$)	h_{FE}	10	—	60	—
---------------------------------------------------------------	----------	----	---	----	---

DYNAMIC CHARACTERISTICS

Output Capacitance ($V_{CB} = 28 \text{ V}, I_E = 0, f = 1 \text{ MHz}$)	C_{ob}	—	200	—	pF
----------------------------------------------------------------------------	----------	---	-----	---	----

(continued)

Note : Above parameters , ratings , limits and conditions are subject to change.

ELECTRICAL CHARACTERISTICS — continued

Characteristic	Symbol	Min	Typ	Max	Unit
FUNCTIONAL TESTS					
Common-Emitter Amplifier Power Gain ($V_{CE} = 50\text{ V}$, $P_{out} = 150\text{ W PEP}$, $f = 28\text{ MHz}$, $I_{CQ} = 50\text{ mA}$)	G_{PE}	15	—	—	dB
Load Mismatch ($V_{CE} = 50\text{ V}$, $I_Q = 50\text{ mA}$, $P_{out} = 150\text{ W PEP}$, $f = 28\text{ MHz}$, Load VSWR = $\infty:1$, All Phase Angles)	ψ	No Degradation in Output Power			
Intermodulation Distortion ($V_{CE} = 50\text{ Vdc}$, $P_{out} = 150\text{ W PEP}$, $I_{CQ} = 50\text{ mA}$, $f = 28\text{ MHz}$)	IMD	—	—	-32	dB

Note : Above parameters , ratings , limits and conditions are subject to change.